

EyeM4



Simple and Flexible

- One-click access to iSolarCloud
- One module can manage up to 10 inverters for remote maintenance and control
- Plug and play, easy installation



Convenient O&M

- Built-in Web server for monitoring and configuration, by PC or smartphone browser; no APP required
- Support of plant maintenance by remote Web access, optimized OPEX
- Support of local and remote parameter setting and firmware updates



Communication

Max. number of devices	10
LED display	LED x 3

Wireless communication

4G communication	LTE(FDD): B1, B3, B5, B8
	LTE(TDD): B38, B39, B40, B41
	TD-SCDMA: B34, B39
	CDMA: BC0
WiFi communicatoin	GSM:900MHz / 1800MHz
	WCDMA:B1, B8
	802.11 b / g / n / ac
	HT20 / 40 / 80 MHz
	2.4 GHz / 5 GHz

Ordering information

EyeM4A	Support of 4G and WiFi wireless communication Apply to China, India, Malaysia
EyeM4B	Support of 4G wireless communication Apply to China
EyeM4C	Support of WiFi wireless communication Apply to Global

Power Supply

DC input	5 VDC, 0.8 A
Power consumption	<4 W

Ambient conditions

Operating Temperature	-30 °C ~ 60 °C
Relative air humidity	≤95 % (non-condensing)
Elevation	≤4000 m
Protection class	IP66

Mechanical parameters

Dimensions (W * H * D)	48 mm * 130 mm * 36 mm
Mounting type	Plug and Play

