

# SUNNY HIGHPOWER PEAK3

SHP 100-21 / SHP 150-21 / SHP 172-21 / SHP 180-21



Premium Monitoring-Service  
**SMA SMART CONNECTED**

## Efficient

- High power density with 180 kW thanks to its compact structure
- Max. yield due to possible DC/AC ratio of up to 200%

## Reliable

- Superior PV system availability with 180 kW units
- Innovative digital features aligned with the energy management platform ennexOS

## Flexible

- For DC input voltages up to 1500 V
- Flexible DC solutions with customer-specific PV array junction boxes

## Easy to install

- Ergonomic handling and simple connection for quick installation
- Centralized commissioning and control of the PV power plant via SMA Data Manager

## SUNNY HIGHPOWER PEAK3

Customized for tomorrow today

The Sunny Highpower PEAK3 is the central component of the SMA solution for PV power plants with a decentralized architecture and system voltages of 1500 V DC. This compact string inverter enables cost-optimized solutions for industrial PV applications thanks to its high power density. It also provides a simple way of transport and allows for quick installation and commissioning. This string inverter with 180 kW of power is equipped with the automatic SMA Smart Connected service for proactive servicing that facilitates operation and maintenance and reduces service costs throughout the entire project lifetime.

Technical Data	Sunny Highpower 100-21	Sunny Highpower 150-21
<b>Input (DC)</b>		
Max. PV array power	200 kWp	300 kWp
Max. input voltage	1000 V	1500 V
MPP voltage range / rated input voltage	590 V to 1000 V / 590 V	880 V to 1450 V / 880 V
Max. input current / max. short-circuit current	180 A / 325 A	
Number of independent MPP trackers	1	
Number of inputs	1 or 2 (optional) for external PV array junction boxes	
<b>Output (AC)</b>		
Rated power at nominal voltage	100 kW	150 kW
Max. apparent power	100 kVA	150 kVA
Nominal AC voltage / AC voltage range	400 V / 177 V to 477 V	600 V / 480 V to 690 V
AC grid frequency / range	50 Hz / 44 Hz to 55 Hz 60 Hz / 54 Hz to 66 Hz	
Rated grid frequency	50 Hz	
Max. output current	151 A	
Power factor at rated power / displacement power factor adjustable	1 / 0 overexcited to 0 underexcited	
Harmonic (THD)	< 3%	
Feed-in phases / AC connection	3 / 3-PE	
<b>Efficiency</b>		
Max. efficiency / European efficiency	98.7% / 98.4%	99.1% / 98.8%
<b>Protective devices</b>		
Ground fault monitoring / grid monitoring / DC reverse polarity protection	● / ● / ●	
AC short-circuit current capability / galvanically isolated	● / –	
All-pole-sensitive residual-current monitoring unit	●	
Monitored surge arrester (type II) AC / DC	● / ●	
Protection class (according to IEC 62109-1) / overvoltage category (as per IEC 62109-1)	I / AC: III; DC: II	
<b>General Data</b>		
Dimensions (W / H / D)	770mm / 830 mm / 462 mm (30.3 in / 32.7 in / 18.2 in)	
Weight	99 kg (218 lb)	
Operating temperature range	-25°C to +60°C (-13°F to +140°F)	
Noise emission (typical)	69 dB(A)	
Self-consumption (at night)	< 5 W	
Topology	transformerless	
Cooling method	OptiCool, active cooling, speed-controlled fan	
Degree of protection (according to IEC 60529)	IP65	
Max. permissible value for relative humidity (non-condensing)	100%	
<b>Features / function / accessories</b>		
DC connection / AC connection	Terminal lug (up to 300 mm <sup>2</sup> ) / Screw terminal (up to 150 mm <sup>2</sup> )	
LED indicators (Status / Fault / Communication)	●	
Ethernet interface	● (2 ports)	
Data interface: SMA Modbus / SunSpec Modbus / Speedwire	● / ● / ●	
Mounting type	Rack mounting	
OptiTrac / Integrated Plant Control / Q on Demand 24/7	● / ● / ●	
Off-grid capable / SMA Fuel Save Controller compatible	● / ●	
Warranty: 5 / 10 / 15 / 20 / 25 years	● / ○ / ○ / ○ / ○	
Certificates and approvals (pending)	IEC/EN 62109-1/-2, VDE-AR-N 4110/4120, IEC 62116, IEC 61727, EN 50549, C10/11, CEI 0-16, G99/1 (>16A), PO 12.3, ABNT NBR 16149	
Type designation	SHP 100-21	SHP 150-21

● Standard features ○ Optional features – Not available Data at nominal conditions Status: 09/2022

Technical Data	Sunny Highpower 172-21	Sunny Highpower 180-21
<b>Input (DC)</b>		
Max. PV array power	344 kWp	360 kWp
Max. input voltage	1500 V	1500 V
MPP voltage range / rated input voltage	968 V bis 1450 V / 968 V	1012 V bis 1450 V / 1012 V
Max. input current / max. short-circuit current	180 A / 325 A	
Number of independent MPP trackers	1	
Number of inputs	1 or 2 (optional) for external PV array junction boxes	
<b>Output (AC)</b>		
Rated power at nominal voltage	172 kW	180 kW
Max. apparent power	172 kVA	180 kVA
Nominal AC voltage / AC voltage range	660 V / 528 V to 759 V	690 V / 552 V to 793 V
AC grid frequency / range	50 Hz / 44 Hz to 55 Hz 60 Hz / 54 Hz to 66 Hz	
Rated grid frequency	50 Hz	
Max. output current	151 A	
Power factor at rated power / displacement power factor adjustable	1 / 0 overexcited to 0 underexcited	
Harmonic (THD)	< 3%	
Feed-in phases / AC connection	3 / 3-PE	
<b>Efficiency</b>		
Max. efficiency / European efficiency	99.2% / 98.9%	99.2% / 98.9%
<b>Protective devices</b>		
Ground fault monitoring / grid monitoring / DC reverse polarity protection	● / ● / ●	
AC short-circuit current capability / galvanically isolated	● / –	
All-pole-sensitive residual-current monitoring unit	●	
Monitored surge arrester (type II) AC / DC	● / ●	
Protection class (according to IEC 62109-1) / overvoltage category (as per IEC 62109-1)	I / AC: III; DC: II	
<b>General Data</b>		
Dimensions (W / H / D)	770mm / 830 mm / 462 mm (30.3 in / 32.7 in / 18.2 in)	
Weight	99 kg (218 lb)	
Operating temperature range	-25 °C to +60 °C (-13 °F to +140 °F)	
Noise emission (typical)	69 dB(A)	
Self-consumption (at night)	< 5 W	
Topology	transformerless	
Cooling method	OptiCool, active cooling, speed-controlled fan	
Degree of protection (according to IEC 60529)	IP65	
Max. permissible value for relative humidity (non-condensing)	100%	
<b>Features / function / accessories</b>		
DC connection / AC connection	Terminal lug (up to 300 mm <sup>2</sup> ) / Screw terminal (up to 150 mm <sup>2</sup> )	
LED indicators (Status / Fault / Communication)	●	
Ethernet interface	● (2 ports)	
Data interface: SMA Modbus / SunSpec Modbus / Speedwire	● / ● / ●	
Mounting type	Rack mounting	
OptiTrac / Integrated Plant Control / Q on Demand 24/7	● / ● / ●	
Off-grid capable / SMA Fuel Save Controller compatible	● / ●	
Warranty: 5 / 10 / 15 / 20 / 25 years	● / ○ / ○ / ○ / ○	
Certificates and approvals (pending)	IEC/EN 62109-1/-2, VDE-AR-N 4110/4120, IEC 62116, IEC 61727, EN 50549, C10/11, CEI 0-16, G99/1 (>16A), PO 12.3, ABNT NBR 16149	
Type designation	SHP 172-21	SHP 180-21

● Standard features ○ Optional features – Not available Data at nominal conditions Status: 09/2022

