





Product Service

# CERTIFICATE

No. Z2 099333 0055 Rev. 03

## Model(s):

LR6-72HV-xxxM, (xxx=320 to 350 in step of 5)  
 LR6-60HV-xxxM, (xxx=270 to 300 in step of 5)  
 LR6-72PH-xxxM, (xxx=340 to 385 in step of 5)  
 LR6-60PH-xxxM, (xxx=280 to 320 in step of 5)  
 LR6-72HPH-xxxM, (xxx=350 to 405 in step of 5)  
 LR6-72HIH-xxxM, (xxx=350 to 405 in step of 5)  
 LR6-60HPH-xxxM, (xxx=295 to 335 in step of 5)  
 LR6-60HIH-xxxM, (xxx=295 to 335 in step of 5)  
 LR6-72OPH-xxxM, (xxx=385 to 400 in step of 5)  
 LR6-60OPH-xxxM, (xxx=335 to 350 in step of 5)  
 LR6-72HPH-xxxMC, (xxx=375 to 390 in step of 5)  
 LR6-60HPH-xxxMC, (xxx=305 to 325 in step of 5)  
 LR4-72HPH-xxxM, (xxx=400 to 460 in step of 5)  
 LR4-72HIH-xxxM, (xxx=400 to 460 in step of 5)  
 LR4-60HPH-xxxM, (xxx=330 to 380 in step of 5)  
 LR4-60HIH-xxxM, (xxx=330 to 380 in step of 5)  
 LR4-72ZPH-xxxM, (xxx=420 to 435 in step of 5)  
 LR4-60ZPH-xxxM, (xxx=350 to 365 in step of 5)  
 LR6-60ZPH-xxxM, (xxx=330 to 355 in step of 5)  
 xxx is standing for rated output power at STC

## Parameters:

Severity of	
Salt Mist Test:	Severity 6 and severity 1
Application Class:	Class A
Maximum System Voltage:	1500 V DC
Fire Safety Class:	Class C
Construction:	Framed, with Junction box, cable and connector.

## Tested according to:

IEC 61215:2005  
 IEC 61730-1:2004  
 IEC 61730-1:2004/AMD1:2011  
 IEC 61730-1:2004/AMD2:2013  
 IEC 61730-2:2004  
 IEC 61730-2:2004/AMD1:2011  
 IEC 61701:2011

## Production Facility(ies):

096558, 002875, 001192, 090968, 099626, 099605, 099606, 097323, 102892, 103410, 103841

TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD  
 ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFICAT

A4 / 07.17